



APC Smart-UPS RT 3000VA 230V Isolation Transformer

SURT001

Call for More Information 19775

- Includes: Installation guide, Mounting hardware, User manual

Output

Nominal Output Voltage	230V
Other Output Voltages	220
Output Connections	(1) IEC 320 C19 (1) IEC Jumpers (1) IEC 60320 C19

Input

Nominal Input Voltage	230V
Input frequency	50/60 Hz
Input Connections	IEC 60320 C20
Number of Power Cords	1
Load Capacity	3000VA
Maximum Input Current	16A

Physical

Maximum Height	130MM, 13.0CM
Maximum Width	432MM, 43.2CM
Maximum Depth	660MM, 66.0CM
Rack Height	3U
Net Weight	56.82KG
Shipping weight	63.64KG
Shipping Height	347MM, 34.7CM
Shipping Width	603MM, 60.3CM

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.

Technical Specifications

Physical	
Shipping Depth	980MM, 98.0CM
Color	Black
Units per Pallet	6.0

Environmental	
Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 3048meters
Storage Temperature	-25 - 65 °C
Storage Elevation	0 - 15240meters

Conformance	
Approvals	C-Tick, CE, EN 50091-1, EN 55022 class B, EN 55024, EN 60950, EN 61000-3-2
Standard warranty	2 years repair or replace

Sustainable Offer Status	
RoHS	Compliant

Disclaimer: Documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user's applications.